



# **BEC ES08**

**8 ports Green Ethernet Desktop Switch**

## **User Manual**

## Introduction

The device is a powerful, high-performance Fast Ethernet switch, with all ports capable of 10 or 100Mbps auto-negotiation operation (NWay), which means the switch could automatically negotiate with the connected partners on the network speed and duplex mode. It is ideal for micro-segmenting large networks into smaller, connected subnets for improved performance, enabling the bandwidth demanding multimedia and imaging applications. Compared to the shared 10Mbps or 100Mbps networks, the switch delivers a dedicated 10/100Mbps connection to every attached client with no bandwidth congestion issue. This switch also supports auto MDI / MDI-X function. Each port could be used to connect to another switch or hub with no crossover RJ-45 cable.

Store-and-forward switching mode promises the low latency plus eliminates all the network errors, including runt and CRC error packets. To work under full-duplex mode, transmission and reception of the frames can occur simultaneously without causing collisions as well as double the network bandwidth.

The switch is plug-n-play without any software to configure and also fully compliant with all kinds of network protocols. Moreover, the rich diagnostic LEDs on the front-panel can provide the operating status of individual port and whole system.

Before you start to install the switch, check the following contents in this package :

- One NWay switch
- One external power adapter
- User's manual


**LED Definition**

Please refer to the following table for LED definition



LED	Status	Operation
Power	Steady Green	Power is on
	Off	Power is off
Link/Act	Steady Green	The port is connected
	Blinking Green	The port is transmitting/receiving data.
	Off	No connection

Rear Panel



**Stations Connection**

Connect each station to the switch by twisted-pair cable. Plug one RJ-45 connector into a RJ-45 port of the switch, and plug the other RJ-45 connector into the station's network adapter. Power on the switch and then system is ready.

For cable selection, refer to the following table.

**Switches Connection**

In making a switch interconnection, you could use any port to connect another switch with straight or crossover cable. As all the ports support auto MDI / MDI-X function, using a straight cable to make a switch-to-switch connection is allowed.

For cable selection, refer to the following table :

Network Speed	Cable Type	Max. Length
10Mbps	Cat. 3, 4, 5 UTP/STP	100 meters
100Mbps	Cat. 5 UTP/STP	100 meters

**Specification**

Standard	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x full duplex operation and flow control
Interface	8* 10/100Mbps RJ-45 Fast Ethernet Ports
Uplink	Auto MDI/MDI-X ( Auto crossover )
Network Speed	10/100Mbps & Full/Half duplex mode auto detection
MAC Address Table	1K MAC address entries
Memory	768 K bits
Power Supply	External Power adapter 5VDC 0.6A
EMI	CE, FCC and VCCI class B

## FCC Certifications



This Equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio

communications.

Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received; including interference that may cause undesired operation.

**CE Mark Warning**



This equipment complies with the requirements relating to electromagnetic compatibility, EN 55022 class B for ITE, the essential protection requirement of Council Directive 89/336/EEC on the approximation of the laws of the Member States relating to electromagnetic compatibility.

Company has an on-going policy of upgrading its products and it may be possible that information in this document is not up-to-date. Please check with your local distributors for the latest information. No part of this document can be copied or reproduced in any form without written consent from the company.

**Trademarks:**

All trade names and trademarks are the properties of their respective companies.  
Copyright © 2009, All Rights Reserved.

## **Product Support and Contact Information**

If you cannot resolve the problem please contact the dealer where you purchased this product.

**Contact BEC**

**WORLDWIDE**

<http://www.bectechnologies.com>