

# M600 5G Series

## High-Performance Industrial/In-Vehicle Router

3GPP Rel-16	5G NR sub-6 GHz	NSA / SA Modes	4G LTE Cat. 19	IP40	Carrier Aggregation	BECentral® CloudEdge
Dual-SIM	802.11ac 802.11n	Firewall	VPN	EN50155*	M12 X-coded*	FAKRA*

\*on select models

### Ideal Use Cases

- Industrial IoT (IIoT)
- Transport & Logistics
- Energy & Utilities
- Private Networks
- Smart Cities
- Mission Critical
- Public Safety

The BEC M600 5G Industrial/In-Vehicle Router Series delivers exceptional 5G performance and reliability. Engineered for resilience in demanding environments, it accommodates diverse applications, from transportation and in-vehicle use to the ever-evolving IoT/M2M landscapes. It features a compact and rugged design, seamlessly integrating dual SIMs, a four-port Gigabit Switch, High-Power Wi-Fi 5, an embedded multi-GNSS receiver for GPS or GLONASS, and ignition sensing for in-vehicle applications. Additionally, it boasts enterprise-level features such as dynamic routing, advanced security measures, Quality of Service (QoS), integrated VPN, and auto-failover, ensuring unparalleled uptime and network redundancy.

Whether managing a vehicle fleet or an intricate IoT network, the M600 5G Router Series is the dependable choice, offering a seamless, high-performance, and reliable connectivity experience.



M600 5G

### 5G Performance and Enhanced Capacity

Designed for performance, the 3GPP Release 16 compliant platform that delivers lower latency and enhanced network connectivity with standalone access (SA), two-carrier sub-6 GHz aggregation, non-standalone access (NSA) dual connectivity, and up to five carrier aggregation for LTE. This single platform offers the flexibility of quick deployment for any 5G or LTE network.

### High Availability and Network Resilience

The M600 5G is a robust industrial router with advanced network processing, multi-WAN connectivity, and built-in features for reliability. It seamlessly handles connectivity issues by automatically redirecting traffic from the primary to the secondary WAN interface in case of failure, and it supports carrier network redundancy through dual SIMs.

### High Performance & Support for 5G NR & LTE Networks

- 5G NR  
3GPP Release 16 Compliant  
SA: 2.4 Gbps (DL) / 900 Mbps (UL)  
NSA: 3.4 Gbps (DL) / 550 Mbps (UL)
- 4G/LTE Cat.19  
: LTE: 5CA DL / 2CA UL (Carrier Aggregation)  
: Peak Data Rate: 1.6 Gbps (DL) / 200 Mbps (UL)  
(The presented data rates are theoretical only, and the actual value depends on network conditions.)

### Enterprise Class Routing and Secured VPN

- BGP and OSPF Dynamic Routing Protocols
- IPSec, GRE, L2TP, PPTP and OpenVPN
- Advanced secure and simultaneous VPN connections
- Advanced Quality of Service (QoS) Framework

### Durable and Versatile Interface Connectivity

Models equipped with FAKRA and M12 connectors contribute to the overall durability and efficiency of the platform. FAKRA connectors in cellular, GPS, and Wi-Fi interfaces ensure a secure, stable connection, minimizing signal issues. M12 connectors, resistant to dust and water, provide a reliable, enduring solution, especially in challenging environments.

### BECentral® CloudEdge Services

BECentral® CloudEdge, an industry-leading cloud-based service, accelerates LTE and 5G Wireless WAN connectivity for deployments of any size. This platform offers zero-touch provisioning, real-time analytics, detailed reporting, historical analysis, performance monitoring, proactive alerts, and API extensibility for third-party integration.

### Carrier-Grade Wireless-LAN

- Compliant with IEEE 802.11a/b/g/n/ac standards
- Simultaneous Dual-Band Wireless up to 2400Mbps
- 4x4 802.11a/n/ac (5GHz) and 3x3 802.11b/g/n (2.4GHz)
- High Transmit Power Design
- Wi-Fi Hotspot with Captive Portal
- Multiple SSID with Client Isolation

### Durable Industrial-Grade Enclosure

- IP40 enclosure for protection against dust and water ingress
- Designed to withstand high temperatures, vibrations, and sudden impacts
- Small form factor with optional mounting kits
- Ignition power control option when mounted within vehicles

# M600 5G Series

## High-Performance Industrial/In-Vehicle Router

### Features & Specifications

#### Supported Frequency Band<sup>\*1</sup>

##### 5G NR sub-6 GHz (3GPP Rel-16)

**Band(NA/NSA)** n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n26, n28, n29, n30, n38, n40, n41, n48, n66, n70, n71, n75, n76, n77, n78, n79

**Carrier Aggregation** sub-6 GHz (FDD+FDD, TDD+TDD, FDD+TDD 2CA)

**Max. Transmission Data Rate** NSA: 3.4Gbps DL / 550Mbps UL  
SA: 2.4Gbps DL / 900Mbps UL

##### 4G LTE (CAT 19 DL / CAT 18 UL)

**Band(FDD/TDD)** 1, 2, 3, 4(66), 5(18,19,26), 7, 8, 12(17), 13, 14,20, 25, 26, 28, 29, 30, 32, 34, 38, 39, 40, 41, 42, 43, 46(LAA), 48, 71

**Carrier Aggregation** 5CA DL / 2CA UL

**Max. Transmission Data Rate** 1.6Gbps DL / 200Mbps UL

#### Network Protocols and Features

- Dual WAN Failover/ Failback
- Dual WAN Load Balancing
- IPv4, IPv6, IPv4/IPv6 dual stack<sup>\*2</sup>
- Dual APN<sup>\*2</sup>
- Keep Alive
- IP Pass-Through
- NAT, Virtual Server and DMZ
- Static Routing, Dynamic Routing (RIP v1/v2, OSPF, BGP)
- SNTP, DNS relay and DDNS
- Universal Plug and Play (UPnP) compliant
- Supports DHCP server/client/relay

#### Virtual Private Network (VPN)

- IPsec
- PPTP
- L2TP
- GRE
- OpenVPN

#### Wireless LAN

- Compliant with IEEE 802.11a/b/g/n/ac standard
- Concurrent dual-band 802.11a/n/ac (5GHz) and 802.11b/g/n (2.4GHz)
- Up to 1733Mbps wireless operation rate at 5GHz
- Up to 600Mbps wireless operation rate at 2.4GHz
- Wi-Fi security with WEP 64/128, WPA-PSK, WPA2-PSK, Mixed WPA/WPA2-PSK
- WPS (Wi-Fi Protected Setup) for easy setup
- Multiple SSIDs
- Supports WDS repeater function
- Wireless MAC Filtering
- Wi-Fi Client Isolation
- Wi-Fi Hotspot with Captive Portal
- Support RADIUS authentication
- Wi-Fi client rate-limiting

#### Global Navigation Satellite System (GNSS)<sup>\*3</sup>

- Embedded multi-GNSS engine for GPS or GLONASS system

#### Firewall

- Built-in NAT Firewall
- Stateful Packet Inspection (SPI)
- Prevents DoS attacks including Land Attack, Ping of Death, etc.
- Access Control
- IP Filtering, MAC Filtering, URL Filtering
- VPN Pass-through

#### Management

- Password protection for system management
- Web-based GUI for remote and local management
- Firmware upgrade and configuration data upload and download via web-based GUI
- CWMP(TR-069)<sup>\*2</sup>, SNMP
- Cellular data usage allowance
- Remote System Log monitoring
- Scheduling Auto-Reboot
- Physical layer/protocol diagnostic test tool
- BECentral® Cloud-Based Remote Management

#### USB Application

- Storage/NAS: embedded FTP server, SAMBA server

#### Hardware Specifications

- WAN: 5G NR sub-6GHz (and/or GbE WAN)
- Ethernet LAN: four (4) RJ-45 port 10/100/1000Mbps auto-crossover (MDI/ MDI-X) switch
- USB 2.0 Host: one (1) port
- SIM Card: two (2) 2FF mini-SIM slot
- Reset Button
- Power Connector: 4-pin connector with ignition sensing
- LED Indicators
- Antenna:
  - 5G NR(FR1): four (4) detachable antennas
  - Wi-Fi: four (4) detachable dual-band antennas
  - GPS: one (1) detachable active antenna (option)

#### Physical Interface

#### External Connector

- 5G NR: SMA x four (4)
- Ethernet: RJ-45 x four (4)
- Wi-Fi: RP-SMA x four (4)
- GNSS: SMA x one (1)
- USB: Type A x one (1)
- SIM: mini-SIM(2FF) slot with cover x two (2)

#### Power Specifications

Input: DC 10V~56V

#### Physical Specifications

199.2 x 132.7 x 46.6 mm (199.2 x 149.1 x 46.6 mm - antenna connector protrusion included)

#### Operating Requirements

- Operating: -40°C to 60°C
- Humidity: 20 ~ 95% non-condensing

#### Notes:

- \*1. The 5G NR/4G LTE is dependent on your local service provider.
- \*2. Only upon request for Telco/ ISP tender projects.
- \*3. The support for GPS and/or GLONASS functions depends on the equipped module's capabilities.

### I/O Specification

#### M600 5G



#### M600-M12 5G



#### M600-M12-FA 5G

